

PA Amplifier with USB/SD & FM & Blue Tooth

EA-120A (120W)

Features:

- ✓ Compact mini size public address amplifier
- ✓ Ideal for classroom sound system use
- ✓ Built-in 100V/70V transformer technology
- ✓ Tabletop amplifier with Mp3 player, FM radio & blue tooth
- ✓ Rate power output at 30W, 60W to 120W.
- ✓ Speaker output of 100V or 70V & 4Ohms-8 Ohms-16 Ohms
- ✓ Mp3 player with USB/SD input on front panel, IR remote control for Mp3 player, FM radio and blue tooth
- ✓ LED indicators for power, clip, protect and signal
- ✓ Mic1-3 and line 1-2 and telephone input. Mic1 of balanced XLR input with phantom power on rear panel. Mic2-3 microphone or line switchable unbalanced 6.3mm phone jack input. Line 1-2 input of RCA input and one RCA line output. Telephone input with VOX priority and MOH (Music on Hold).
- ✓ Volume control for Mic1-3, line1-2, Mp3/FM, bass/treble and master
- ✓ With short-circuit, clip, overload and high temp protection
- ✓ AC220V or 115V & 24V DC both operation system



Specification:

| | |
|--------------------|---|
| Model | EA-120A |
| Description | PA Amplifier with USB/SD & FM & Blue Tooth |
| Rated Power Output | 120W |
| Speaker Outputs | 100V or 70V & 4Ohms-8 Ohms-16 Ohms |
| Connector | Mic1 input by balanced XLR with phantom power Input2-3 inputs Mic/Line switchable unbalanced 6.3mm phone jack Line1-2 inputs by RCA; Line output by RCA |
| Attenuation | Microphone1-3, line1-2 and Mp3/FM, bass/treble and master |
| Input | MIC1-3: 5-8mV, 600 Ω ; Line, 150-470mV, 10K Ω , unbalanced RCA |
| Line Out | 0.775(0dBV) |
| Frequency Response | 60Hz-15kHz(±3dB) |
| S/N Ratio | Line ≥ 85dB, Mic≥ 72dB |
| THD | Less than 0.5% |
| Protection | short-circuit, clip, overload and high temp protection |
| Power Consumption | 200W |
| Power Supply | AC220V or 115V & 24V DC /50-60Hz |
| Dimension | 320(W)×210(D)×90(H)mm |
| Weight | 4.9kg |

Rear Panel:

